



**Art. No.: 31112**  
**Ambus EasySwitch**  
**holder for cylindrical fuses 10 x 38**  
**2-pole**

**Product Group : 17**  
**Subgroup : 06**

**Standards :**

IEC / EN 60947-3  
IEC / EN 60269-2-1(III)  
UL 512  
CSA C22.2 No. 39

**Approvals :**

IEC (CB), GOST, CCC, CSA, UL

Type No.: AES10x38  
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT2, [www.ul.com](http://www.ul.com)  
CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>  
CCC certificate: 2004010302117255

**Electrical Data :**

IEC, EN : 32 A, 690 V (50-60 Hz)  
UL, CSA : 30 A, 600 V (60 Hz)  
rated insulation voltage : 800 V  
utilisation category to IEC 60947-3  
AC-22B (400 V)

**Electrical Data :**

conditional rated short circuit current 50 kA with fuse links gG

for fuse links to IEC 60269-2-1(III) with rated power dissipation:

max. 3 W gG/gL

max. 1,2 W aM

Power dissipation at nominal current: 0,6 Watt

**Mechanical Data :**

Width x Height x Depth (mm): 36 x 81 x 58

Weight (kg/100): 12,8

Fastening method:

clip-on mounting

**Connections :**

box terminal :

1,5 - 25 mm<sup>2</sup> / AWG 14 - AWG 4

flexible cables, directly or with wire-end ferrule

Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

**Versions :**

version with luminous indication : part no. 31132

version for semiconductor protection : part no. 31276

**Pack Size : 6**

**Catalog 2006 :**

Page: 6/5

**Accessories to Article 31112 :**



31939 label for AES  
100x 10 pcs.