



**Art. No.: 31113**  
**Ambus EasySwitch**  
**holder for cylindrical fuses 10 x 38**  
**3-pole**

**Product Group : 17**  
**Subgroup : 06**

**Standards :**

IEC / EN 60947-3  
IEC / EN 60269-2-1(III)  
UL 512  
CSA C22.2 No. 39

**Approvals :**

IEC (CB), GOST, CCC, CSA, UL

Type No.: AES10x38  
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT2, [www.ul.com](http://www.ul.com)  
CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>  
CCC certificate: 2004010302117255

**Electrical Data :**

IEC, EN : 32 A, 690 V (50-60 Hz)  
UL, CSA : 30 A, 600 V (60 Hz)  
rated insulation voltage : 800 VV  
utilisation category to IEC 60947-3  
AC-22B (690 V)

**Electrical Data :**

conditional rated short circuit current with fuse links gG  
100 kA (500 V)  
80 kA (690 V)

for fuse links to IEC 60269-2-1(III) with rated power dissipation:

max. 3 W gG/gL

max. 1,2 W aM

Power dissipation at nominal current: 0,9 Watt

**Mechanical Data :**

Width x Height x Depth (mm): 54 x 81 x 58

Weight (kg/100): 19,3

Fastening method:

clip-on mounting

**Connections :**

box terminal :

1,5 - 25 mm<sup>2</sup> / AWG 14 - AWG 4

flexible cables, directly or with wire-end ferrule

Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

**Versions :**

version with luminous indication : part no. 31133

version for semiconductor protection : part no. 31277

**Pack Size : 4**

**Catalog 2006 :**

Page: 6/5

**Accessories to Article 31113 :**



31027 end cap  
for 3-pole comb type busbars 16 mm<sup>2</sup>



31102 comb type busbar, insulated, 3-pole, bridge type  
65 A, pitch 27 mm, 1 m long

**Accessories to Article 31113 :**



31103 connecting terminal, side connection  
for comb type busbars pitch 18 mm



31157 connecting terminal, front connection  
for comb type busbars pitch 18 mm



31939 label for AES  
100x 10 pcs.