



Art. No.: 31284
Ambus J-Carrier
holder for cylindrical fuses Class J, 30 A
1-pole

Product Group : 16
Subgroup : 03

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AJC 30
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

Electrical Data :
30 A, 600 V (60 Hz)
rated insulation voltage : 800 V
for fuse links Class J to UL 248-8

Mechanical Data :
Width x Height x Depth (mm): 36 x 115 x 69
Weight (kg/100): 15,8
Fastening method:
clip-on mounting

Connections :

box terminal :

2,5 - 50 mm² / AWG 14 - AWG 1

flexible cables, directly or with wire-end ferrule

Md 3,5 - 4,0 Nm / 31 - 35 lb.in.

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Versions :

2P : part no. 31285

3P : part no. 31287

Pack Size : 6

Catalog 2006 :

Page: 6/12

Accessories to Article 31284 :



31939 label for AES
100x 10 pcs.