

**Art. No.: 31921**  
**Ambus J-Carrier**  
**holder for cylindrical fuses Class J, 60 A**  
**2-pole**  
**New Article**

**Product Group : 16**  
**Subgroup : 06**

**Standards :**  
UL 512  
CSA C22.2 No. 39

**Approvals :**  
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AJC 60  
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, [www.ul.com](http://www.ul.com)  
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

**Electrical Data :**  
60 A, 600 V (60 Hz)  
rated insulation voltage : 800 V  
for fuse links Class J to UL 248-8

**Mechanical Data :**  
Width x Height x Depth (mm): 80 x 118 x 82  
Weight (kg/100): 37  
Fastening method:  
clip-on mounting

**Connections :**  
box terminal :  
6 - 50 mm<sup>2</sup> / AWG 10 - AWG 1  
flexible cables, directly or with wire-end ferrule  
Md 3,5 - 4,0 Nm / 31 - 35 lb.in.  
(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

**Versions :**  
1P : part no. 31920  
3P : part no. 31922

**Pack Size : 3**


**Catalog 2006 :**  
Page: 6/12

**Accessories to Article 31921 :**

kein Produktbild verfügbar  no picture available	31360 fuse link 35 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar  no picture available	31361 fuse link 40 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar  no picture available	31362 fuse link 45 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar  no picture available	31363 fuse link 50 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar  no picture available	31364 fuse link 60 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar  no picture available	31511 fuse link 35 A, fast acting 600 V AC, 300 V DC
kein Produktbild verfügbar  no picture available	31512 fuse link 40 A, fast acting 600 V AC, 300 V DC

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

**Accessories to Article 31921 :**



31513 fuse link 45 A, fast acting  
600 V AC, 300 V DC



31514 fuse link 50 A, fast acting  
600 V AC, 300 V DC



31515 fuse link 60 A, fast acting  
600 V AC, 300 V DC



31939 label for AES  
100x 10 pcs.