

Art. No.: 31922
Ambus J-Carrier
holder for cylindrical fuses Class J, 60 A
3-pole
New Article

Product Group : 16
Subgroup : 06

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: AJC 60
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 6225-01, <http://directories.csa-international.org>

Electrical Data :
60 A, 600 V (60 Hz)
rated insulation voltage : 800 V
for fuse links Class J to UL 248-8

Mechanical Data :
Width x Height x Depth (mm): 120 x 118 x 82
Weight (kg/100): 55,9
Fastening method:
clip-on mounting

Connections :
box terminal :
6 - 50 mm² / AWG 10 - AWG 1
flexible cables, directly or with wire-end ferrule
Md 3,5 - 4,0 Nm / 31 - 35 lb.in.
(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Versions :
1P : part no. 31920
2P : part no. 31921

Pack Size : 2


Catalog 2006 :
Page: 6/12

Accessories to Article 31922 :

kein Produktbild verfügbar no picture available	31360 fuse link 35 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar no picture available	31361 fuse link 40 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar no picture available	31362 fuse link 45 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar no picture available	31363 fuse link 50 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar no picture available	31364 fuse link 60 A, time delay 600 V AC, 500 V DC
kein Produktbild verfügbar no picture available	31511 fuse link 35 A, fast acting 600 V AC, 300 V DC
kein Produktbild verfügbar no picture available	31512 fuse link 40 A, fast acting 600 V AC, 300 V DC

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

Accessories to Article 31922 :



31513 fuse link 45 A, fast acting
600 V AC, 300 V DC



31514 fuse link 50 A, fast acting
600 V AC, 300 V DC



31515 fuse link 60 A, fast acting
600 V AC, 300 V DC



31939 label for AES
100x 10 pcs.