



Art. No.: 33307
Fuse base Class J 101-200A
panel mounting

Product Group : 16
Subgroup : 12

Standards :
UL 512
CSA C22.2 No. 39

Approvals :
GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: JC200
Duty Tariff No.: 8536 30 30

UL File Number: E230163, Category: IZLT, www.ul.com
CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>

Electrical Data :
3-pole, 600 V a.c.
rated short-circuit current 200 kA
for fuse links Class J to UL 248-8

Mechanical Data :
Width x Height x Depth (mm): 210 x 255 x 100
Weight (kg/100): 339
screw mounting to mounting plate,
terminal 10-150 mm², re, rm, f, f + AE; AWG 8-MCM 300, 16-18 Nm / 142-160 lb.in.

Remarks :
cover cap included

Pack Size : 1

Catalog 2006 :
Page: 6/12

Accessories to Article 33307 :



03218 fuse link 110 A, fast acting
600 V AC, 300 V DC



03219 fuse link 125 A, fast acting
600 V AC, 300 V DC



03220 fuse link 150 A, fast acting
600 V AC, 300 V DC



03221 fuse link 175 A, fast acting
600 V AC, 300 V DC



03222 fuse link 200 A, fast acting
600 V AC, 300 V DC



03232 fuse link 110 A, time delay
600 V AC, 500 V DC

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

Accessories to Article 33307 :



03233 fuse link 125 A, time delay
600 V AC, 500 V DC



03234 fuse link 150 A, time delay
600 V AC, 500 V DC



03235 fuse link 175 A, time delay
600 V AC, 500 V DC



03236 fuse link 200 A, time delay
600 V AC, 500 V DC